

Konstruktion (Betong)	Resultat utan åtgärd		dB3+30 mm avjämning (gipsbaserad)		dB3+30 mm avjämning (cementbaserad)		2 x dB3+30mm avjämning (cementbaserad)		dB1+10 mm avjämning + klinker		dB2+ parkett (14 mm)	dB1+ linoleum (2.5 mm)
	R'w	L'n,w	R'w	L'n,w	R'w	L'n,w	R'w	L'n,w	R'w	L'n,w	L'n,w	L'n,w
Homogena												
200 mm	59	74	62	48	60.5	50.5	63	45	58.5	59.5	54.5	47.5 *
220 mm	60	73	63	47	61	49.5	63.5	43.5	59.5	58	53	46 *
240 mm	61	71.5	63.5	46	62	48.5	64.5	42.5	60.5	57	52	45 *
260 mm	62	70.5	64	45	63	47.5	65	41.5	61.5	56	51	44 *
280 mm	63	70	65	43.5	63.5	46.5	65.5	40.5	62	55	50	43.5 *
300 mm	63.5	69	65.5	43	64	45.5	66	39.5	64	54.5	49.5	42.5 *
HD/F typer												
120/19 (290kg)	54.5	84.5	58.5	53.5	56	56	60	49.5	54	68.5	59	51 *
120/20 (255kg)	53.5	86.5	58	55	55.5	57.5	59.5	51	53	70	60.5	53 *
120/20 (295kg)	55	84.5	59	53	56.5	55.5	60	49	54.5	68.5	59	51 *
120/20 (330kg)	56	83	59.5	52	57.5	54.5	61	48	55.5	67	57.5	49.5 *
120/27 (365kg)	58	81.5	61	50.5	59	53	62	46.5	57.5	65.5	56.5	48.5 *
120/27 (445kg)	59.5	79	62	48	60.5	50.5	63	44	59	63	54	46 *
120/30 (480kg)	60	78	62.5	47	61	49.5	63.5	43	60	62	53.5	45.5 *